

DIMENSIONS / SHIPPING				
Model	L"	L1"	L2"	Est Wt (lbs)
DP46R.5718A	46.500	48.000	4.625	N/A
DP58R.5718A	62.750	64.250	6.250	N/A
DP610R.5718A	76.000	77.500	6.375	N/A
DP812R.5718A	88.000	89.500	5.875	N/A
DP914R.5718A	101.000	102.500	16.375	N/A

ELECTRICAL															
Model	System Circuit Volts		Ph	Frq	Rated Load Amps	Min Cir Amps	Max OCP Amps	Watts	Wires	NEMA Plug	Amps Lights	Amps Fans	Amps Anti-Sweats	Amps Misc/Refrig/Heat	
DP46R.5718A	Remote (DX)	Circuit #1	110-120	1	60	1.37	15	15	62	2+G	Leads Single	0.70	0.20	0.47	N/A
DP58R.5718A	Remote (DX)	Circuit #1	110-120	1	60	1.97	15	15	76	2+G	Leads Single	0.70	0.70	0.57	N/A
DP610R.5718A	Remote (DX)	Circuit #1	110-120	1	60	2.06	15	15	87	2+G	Leads Single	0.70	0.70	0.66	N/A
DP812R.5718A	Remote (DX)	Circuit #1	110-120	1	60	2.25	15	15	111	2+G	Leads Single	0.70	0.70	0.85	N/A
DP914R.5718A	Remote (DX)	Circuit #1	110-120	1	60	2.35	15	15	126	2+G	Leads Single	0.70	0.70	0.95	N/A

REFRIGERATION														
Model	Zone	Section	System	Envt	REMOTE REFRIGERATION					GLYCOL / R744 REFRIGERATION				
					SST (°F)	Conv. Rack BTUH	Para. Rack BTUH	Defrost Interval (Hrs)	Defrost Duration	Total GPM	Pressure Drop (psi)	Concent (%)	Liquid Temp (°F)	
DP46R.5718A	All	Main	Remote-DX	Type I	20	1,382	1,280	4.00	30.00	N/A	N/A	N/A	N/A	
DP58R.5718A	All	Main	Remote-DX	Type I	20	1,685	1,560	4.00	30.00	N/A	N/A	N/A	N/A	
DP610R.5718A	All	Main	Remote-DX	Type I	20	1,728	1,600	4.00	30.00	N/A	N/A	N/A	N/A	
DP812R.5718A	All	Main	Remote-DX	Type I	20	2,322	2,150	4.00	30.00	N/A	N/A	N/A	N/A	
DP914R.5718A	All	Main	Remote-DX	Type I	20	2,592	2,400	4.00	30.00	N/A	N/A	N/A	N/A	

INTENDED ENVIRONMENT		
WARMEST AVERAGE PRODUCT TEMP & INTENDED USE OF ZONES		
Zone	Temp (°F)	Intended Use
1	38-40	Unpackaged refrigerated products

IMPORTANT NOTES
1) Units must be shimmed during installation to ensure the unit is level and plumb.

REGULATORY	
All Models	Accordance with AHRI Std 1200 ETL Listed to UL 471 ETL Listed to CAN/CSA 22.2 No. 120 ETL Sanitation to NSF/ANSI 7




In Accordance with
AHRI Std 1200


Technical Information

Grocerant - Sandwich Prep Case With Refrigerated Rear Storage - Remote DX

Structural Concepts®
DELIVERING FRESH. ALWAYS.™




CONTROLLER: DP(L)R.5718A.6527,
DP(L)RC.5718A.6527, DP(L)RC.5718A.7716,
DP(L)R.5718A.7716



CONTROLLER: DP914R.5718A.6527,
DP914RC.5718A.6527, DP914RC.5718A.7716,
DP914R.5718A.7716

MODEL	w/ CONTROLLER
DP(L)R.5718A.7716	REMOTE DX w/ DANFOSS
DP(L)RC.5718A.7716	CO2 w/ DANFOSS
DP(L)R.5718A.6527	REMOTE DX w/ DIXELL
DP(L)RC.5718A.6527	CO2 w/ DIXELL
MODEL	w/o CONTROLLER
DP(L)52R.5718A	REMOTE DX
DP(L)52RG.5718A	REMOTE GLYCOL



NOTE: ALL DIMENSIONS APPROXIMATE

⊗ ELECTRICAL JUNCTION BOX
(SUPPLIED WITH 6" LEADS OR POWER CORD).
○ LOCATION OF DRAIN TUBE FOR REMOTE REF.
ONLY (SUPPLIED WITH 3/4" OR 1 1/2" PVC TUBE).

⊕ REFRIGERATION LINE CONNECTION.
⊞ REMOTE FLOOR SINK & UTILITIES
ACCESS AREA.

▨ SELF-CONTAINED CASE SERVICE ACCESS AREA.
▩ DRY CASE SERVICE ACCESS AREA.