

# Technical Information

Structural Concepts®

DELIVERING FRESH. ALWAYS.™

Grocerant - Corner Interaction Counter With Shelving and Sneeze Guard - Self-Service - 90°

| DIMENSIONS / SHIPPING |         |     |       |              |
|-----------------------|---------|-----|-------|--------------|
| Model                 | L"      | L1" | L2"   | Est Wt (lbs) |
| FB90S-CXM1.7862       | 105.125 | N/A | 0.000 | N/A          |

| ELECTRICAL      |                      |     |     |     |     |                 |              |              |       |       |           |             |           |                  |                       |
|-----------------|----------------------|-----|-----|-----|-----|-----------------|--------------|--------------|-------|-------|-----------|-------------|-----------|------------------|-----------------------|
| Model           | System Circuit Volts |     |     | Ph  | Frq | Rated Load Amps | Min Cir Amps | Max OCP Amps | Watts | Wires | NEMA Plug | Amps Lights | Amps Fans | Amps Anti-Sweats | Amps Misc/Refrig/Heat |
| FB90S-CXM1.7862 | N/A                  | N/A | N/A | N/A | N/A | N/A             | N/A          | N/A          | N/A   | N/A   | N/A       | N/A         | N/A       | N/A              | N/A                   |

| REFRIGERATION   |      |         |          |        |                      |                 |                 |                        |                  |                             |                     |             |                  |     |
|-----------------|------|---------|----------|--------|----------------------|-----------------|-----------------|------------------------|------------------|-----------------------------|---------------------|-------------|------------------|-----|
| Model           | Zone | Section | System   | Envt   | REMOTE REFRIGERATION |                 |                 |                        |                  | GLYCOL / R744 REFRIGERATION |                     |             |                  |     |
|                 |      |         |          |        | SST (°F)             | Conv. Rack BTUH | Para. Rack BTUH | Defrost Interval (Hrs) | Defrost Duration | Total GPM                   | Pressure Drop (psi) | Concent (%) | Liquid Temp (°F) |     |
| FB90S-CXM1.7862 | All  | Ambient | None-N/A | Type I | N/A                  | N/A             | N/A             | N/A                    | N/A              | N/A                         | N/A                 | N/A         | N/A              | N/A |

| INTENDED ENVIRONMENT   |  |
|--|--|
| Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise under Envt above. |  |

| IMPORTANT NOTES   |
|---|
| 1) Units must be shimmed during installation to ensure the unit is level and plumb. |

| WARMEST AVERAGE PRODUCT TEMP & INTENDED USE OF ZONES |           |                                    |
|--|-----------|------------------------------------|
| Zone   | Temp (°F) | Intended Use                       |
| 1  | Ambient   | Packaged non-refrigerated products |

| REGULATORY |  |
|------------|--|
| None       |  |



