

Technical Information

Floral - FLP Straight Inside Wrap Open Low Profile LH or RH Case - Remote DX

Structural Concepts®

DELIVERING FRESH. ALWAYS.™

DIMENSIONS / SHIPPING				
Model	L"	L1"	L2"	Est Wt (lbs)
FLP10WL.5589	N/A	114.250	0.000	N/A
FLP10WR.5589	N/A	114.250	0.000	N/A

ELECTRICAL															
Model	System Circuit Volts			Ph	Frq	Rated Load Amps	Min Cir Amps	Max OCP Amps	Watts	Wires	NEMA Plug	Amps Lights	Amps Fans	Amps Anti-Sweats	Amps Misc/Refrig/Heat
FLP10WL.5589	Remote (R404A)-Type I Env	Circuit #1	110-120	1	60	2.05	15	15	199	2+G	Leads Single		1.40	0.65	N/A
FLP10WR.5589	Remote (R404A)-Type I Env	Circuit #1	110-120	1	60	2.05	15	15	199	2+G	Leads Single		1.40	0.65	N/A

REFRIGERATION													
Model	Zone	Section	System	Envt	REMOTE REFRIGERATION					GLYCOL / R744 REFRIGERATION			
					SST (°F)	Conv. Rack BTUH	Para. Rack BTUH	Defrost Interval (Hrs)	Defrost Duration	Total GPM	Pressure Drop (psi)	Concent (%)	Liquid Temp (°F)
FLP10WL.5589	All	Main	Remote-R404A-Type I Env	Type I	26	8,843	8,188	3.00	25.00	N/A	N/A	N/A	N/A
FLP10WR.5589	All	Main	Remote-R404A-Type I Env	Type I	26	8,843	8,188	3.00	25.00	N/A	N/A	N/A	N/A

INTENDED ENVIRONMENT
 Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise under Envt above.

IMPORTANT NOTES
 1) Units must be leveled during installation to ensure the unit is level and plumb.

WARMEST AVERAGE PRODUCT TEMP & INTENDED USE OF ZONES		
Zone	Temp (°F)	Intended Use
1	38	Floral products

REGULATORY	
All Models	Accordance with AHRI Std 1200 ETL Listed to UL 471 ETL Listed to CAN/CSA 22.2 No. 120



In Accordance with
AHRI Std 1200

